

# JSD150


## Description

- 1) Low forward voltage and leakage current
- 2) Low inductance package
- 3) High surge current capability



## Typical Application

- 1) Field supply for DC motors
- 2) Line rectifiers for transistorized AC motor controllers
- 3) Non-controllable rectifiers for AC/DC converter



**Absolute Maximum Ratings** (Packaged into D1, unless otherwise specified,  $T_{CASE}=25^{\circ}\text{C}$ )

Parameter	Test Conditions	Symbol	Values				Unit
			12	16	18	20	
Junction temperature range		$T_J$	-40~+150				°C
Storage temperature range		$T_{STG}$	-40~+125				°C
Repetitive peak reverse voltage		$V_{RRM}$	1200	1600	1800	2000	V
Non-repetitive peak reverse voltage		$V_{RSM}$	1300	1700	1900	2100	V
Output current	$T_c=95^{\circ}\text{C}$	$I_D$	150				A
Forward surge current	1/2 cycle, Sine wave	$I_{FSM}$	1500				A
Value for fusing	50Hz, $T_J=25^{\circ}\text{C}$	$I^2t$	11200				$\text{A}^2\text{s}$
RMS isolation voltage	A.C 50Hz(1s/1min)	$V_{isol}$	3600/3000				V



## Three Phase Rectifier Bridge Module

**Electrical Characteristics** (Packaged into D1, unless otherwise specified,  $T_{CASE}=25^{\circ}\text{C}$ )

Parameter	Test Conditions	Symbol	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	$I_F=150\text{A}, T_J=25^{\circ}\text{C}$	$V_{FM}$	-	-	1.35	V
Reverse leakage current	$V_R=V_{RRM}, T_J=25^{\circ}\text{C}$	$I_{RRM}$	-	-	0.5	mA
	$V_R=V_{RRM}, T_J=150^{\circ}\text{C}$		-	-	10	mA
Threshold voltage	$T_J=150^{\circ}\text{C}$ , for power loss calculation only	$V_{TO}$	-	-	0.8	V
Slope resistance		$r_T$	-	-	3.3	mΩ


**Thermal Characteristics** (Packaged into D1, unless otherwise specified,  $T_{CASE}=25^{\circ}\text{C}$ )

Parameter	Test Conditions	Symbol	Values			Unit
			Min.	Typ.	Max.	
Thermal impedance (junction to case)	Per diode	$R_{th(j-c)}$	-	-	0.75	°C/W
Mounting torque	Module and heatsink fixed torque, screw M5	M	4.25	-	5.75	Nm
	Electrode connection torque, screw M5		4.25	-	5.75	Nm
Weight			132			g
Case style			D1			

### Ordering Information


<u>J</u>	<u>S</u>	<u>D</u>	<u>150</u>	<u>/18</u>	
<u>JieJie Semiconductor Co.,Ltd</u>					<u>12:<math>V_{RSM} \geq 1300\text{V}</math></u> <u>16:<math>V_{RSM} \geq 1700\text{V}</math></u> <u>18:<math>V_{RSM} \geq 1900\text{V}</math></u> <u>20:<math>V_{RSM} \geq 2100\text{V}</math></u>
		<u>Diode module</u>		<u><math>I_D=150\text{A}</math></u>	

## Mechanical Characteristics(mm)




## Performance Curves


**FIG.1:** Forward characteristics(per diode)




**FIG.3:** Forward current vs. case temperature



**FIG.2:** Peak on-state surge current



**FIG.4:** Maximum transient thermal impedance





## Three Phase Rectifier Bridge Module

Information furnished in this document is believed to be accurate and reliable. However, JieJie Semiconductor Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.

Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

This document is the 0.5th version which is made in 5-Aug.-2022. This document supersedes and replaces all information previously supplied.

 is registered trademarks of JieJie Semiconductor Co., Ltd. Copyright©2022 Semiconductor Co., Ltd. Printed All rights reserved.